

# Double Sided Rubber Resin Adhesive Tape

## Product Description

DTR75 is a pressure-sensitive rubber resin adhesive on a roll for bonding difficult substrates such as polyethylene and polypropylene.

It cannot be used in combination with plasticised PVC

## Features

- Clean and economical
- Easy to use straight from the roll
- Very high adhesion

## Typical Applications

- Joining polythene sheeting
- Bonding polypropylene substrates
- Bonding kickplates
- Fixing carpets
- Mounting lightweight items
- Making products self-adhesive

	Value
Adhesive	Rubber resin
Thickness	0.4mm, 1mm, 2mm
Widths	12mm, 19mm, 25mm, 38mm
Tolerances	Thickness and width <10%
Colour	Transparent
Static shear	No movement allowed 250 g/25mm x 25mm @ 20°C
Tensile strength	550 kPa
Elongation	>1000%
Service temperature	-10°C to +40°C
Application temperature	Above +10°C
UV resistance	Poor
Durability	>10 years
Chemical resistance	Chemicals, oil and petrol will affect product
Shelf life	1 year

*Please note: The above technical information is given as a guide and is based on recent test data obtained under laboratory conditions. Materials should be fully tested by the end user to establish suitability of the product for the intended application. March 2024*

## Premier Sealant Systems Ltd.

T 01724 864 100 | E [sales@sealprem.com](mailto:sales@sealprem.com) | [www.sealprem.com](http://www.sealprem.com)

Mercia Way, Foxhills Industrial Park, Scunthorpe, DN15 8RE

Registered Office: Mercia Way, Foxhills Industrial Park, Scunthorpe, DN15 8RE | Registered in Cardiff No. 3000843