

ARBO Façade/AFS Primer

Product Description

AFS Primer is a one part, solvent containing, air-drying polyacrylate/silane blend based primer.

Main Applications

Recommended for use in conjunction with the Arbo Membrane System for use with Arbo SA and Arbo Membrane Adhesive. Recommended for the priming of porous surfaces such as sound concrete, cement boards, timber and other porous surfaces. AFS Primer is easy to apply and very convenient for large surface area applications. Due to the variety of substrates available it is recommended that a trial application is carried out before construction commences.

Instructions

The joint surfaces must be clean, dry and free from all contamination. The surfaces should be degreased using the appropriate Arbo Cleaner. Apply AFS Primer using a clean dry brush or roller and allow to dry for a least 1 hour but not more than 8 hours before applying the adhesive. The joint width should be at least 6mm in order that the joint faces can be cleaned and primed correctly.

Storage Life - 6 months in original unopened package stored in a cool, dry place out of direct sunlight.

Health & Safety – Primer is labeled as harmful and Highly Flammable. For full information please refer to Safety Data Sheet.

Features

- AFS Primer is supplied in 1 litre containers.
- Easy to apply
- Fast dry

	Values
Colour	Colourless
Density	Approx 0.95 g/cm³
Application Temperature	+ 5°C to + 30°C
Cleaning	Tools must be carefully cleaned immediately after use with an appropriate cleaner.

Please note: The above technical information is given as a guide and is based on recent test data obtained under laboratory conditions. Materials should be fully tested by the end user to establish suitability of the product for the intended application. March 2024