

AG2 Porous Primer

Product Description

AG2 Porous Primer is a one part, solvent containing, air drying isocyanate resin-based primer.

Main Applications

Recommended for use in conjunction with Arbokol 2150 two-part polysulphide sealants for the priming of porous surfaces such as concrete, block-work, brickwork etc.

Application Instructions

The joint surfaces must be clean, dry and free from all contamination. The surfaces should be cleaned from any grease using the appropriate Arbo Cleaner. Apply one coat of AG2 Porous primer using a clean dry brush and allow it to dry for a least 1 hour but not more than 8 hours before applying the sealant.

All joint preparation and priming should be carried out in accordance with BS 8000 Part 16, the British Standard for the sealing of joints in buildings using sealants.

The joint width should be at least 6mm in order that the joint faces can be cleaned and primed correctly.

Yield approximately 125 metres per 500ml, 1250 metres per 5 litre.

Storage Life – 9 months in original unopened packaging stored in a cool, dry out of direct sunlight.

Health and Safety – AG2 Porous Primer is labeled as Harmful and Highly Flammable. For full information please refer to Safety Data Sheet.

Features

- Easy to apply
- Quick dry

	Value
Colour	Colourless, yellowish
Density	Approx 1.0 g/cm ³
Application Temperature	+ 5°C to + 30°C
Cleaning	Tools must be carefully cleaned immediately after use with an appropriate cleaner.

Please note: The above technical information is given as a guide and is based on recent test data obtained under laboratory conditions. Materials should be fully tested by the end user to establish suitability of the product for the intended application. March 2024

Premier Sealant Systems Ltd.

T 01724 864 100 | E sales@sealprem.com | www.sealprem.com

Mercia Way, Foxhills Industrial Park, Scunthorpe, DN15 8RE

Registered Office: Mercia Way, Foxhills Industrial Park, Scunthorpe, DN15 8RE | Registered in Cardiff No. 3000843