

High Density Polyethylene

Product Description

Sealprem profiled foam fillers are designed to seal roofing and cladding profiles against dust, water and water vapour ingress.

Features

Sealprem fillers are supplied:

- Made to measure
- With extended base
- Ventilated
- Self-adhesive
- In a range of materials, thicknesses & colours
- In spacer & strip form
- Angle-cut

Typical Applications

- Sealing eaves and ridge
- Sealing hips and valleys
- Sealing rooflights

H60	
Type	High density
Material	Fully closed cell cross-linked PE
Colour	Off-white
Thickness	50mm
Density (kg/m ³)	60
Service temperature (°C)	-60°C to +90°C
Thermal conductivity at 10°C	0.0400 W/mK
Thermal conductivity at 40°C	0.0430 W/mK
Durability (dependent on conditions)	20 years

Please note: The above technical information is given as a guide and is based on recent test data obtained under laboratory conditions. Materials should be fully tested by the end user to establish suitability of the product for the intended application. March 2024

Premier Sealant Systems Ltd.

T 01724 864 100 | E sales@sealprem.com | www.sealprem.com

Mercia Way, Foxhills Industrial Park, Scunthorpe, DN15 8RE

Registered Office: Mercia Way, Foxhills Industrial Park, Scunthorpe, DN15 8RE | Registered in Cardiff No. 3000843