

EPDM

Product Description

Sealprem profiled foam fillers are designed to seal roofing & cladding profiles against dust, water and water vapour ingress.

Features

Sealprem fillers are supplied:

- Made to measure
- Ventilated
- In a range of materials, thicknesses & colours
- With extended base
- In spacer & strip form
- Angle-cut

Typical Applications

- Sealing eaves and ridge
- Sealing hips and valleys
- Sealing rooflights

	E25	E50
Type	EPDM	EPDM
Material	Fully closed-cell EPDM	Fully closed-cell EPDM
Colour	Black or Off White	Black or Off White
Thickness	25mm	50mm
Density (kg/m ³)	Black: 100 - 140 White: 120 - 160	Black: 100 - 140 White: 120 - 160
Service temperature (°C)	Black: -40 to +85 (intermittent to +100) White: -30 to +90 (intermittent to +110)	Black: -40 to +85 (intermittent to +100) White: -30 to +90 (intermittent to +110)
Durability (dependent on conditions)	Up to 25 years	Up to 25 years

Please note: The above technical information is given as a guide and is based on recent test data obtained under laboratory conditions. Materials should be fully tested by the end user to establish suitability of the product for the intended application. March 2024

Premier Sealant Systems Ltd.

T 01724 864 100 | E sales@sealprem.com | www.sealprem.com

Mercia Way, Foxhills Industrial Park, Scunthorpe, DN15 8RE

Registered Office: Mercia Way, Foxhills Industrial Park, Scunthorpe, DN15 8RE | Registered in Cardiff No. 3000843