

Metallocene Polyolefin

Product Description

Sealprem profiled foam fillers are designed to seal roofing and cladding profiles against dust, water and water vapour ingress.

Features

Sealprem fillers are supplied:

- Made to measure
- With extended base
- Ventilated
- In a range of materials, thicknesses & colours
- In spacer & strip form
- Angle-cut

Typical Applications

- Sealing eaves and ridge
- Sealing hips and valleys
- Sealing rooflights

	Black	White
Type	High tensile	High tensile
Material	Fully closed-cell metallocene catalysed polyolefins	Fully closed-cell metallocene catalysed polyolefins
Thickness	25mm +/-2mm	25mm +/-2mm
Density (kg/m ³)	24	33
Service temperature (°C)	-70 to +100	-70 to +100
Durability (dependent on conditions)	25 + years	25 + years

Please note: The above technical information is given as a guide and is based on recent test data obtained under laboratory conditions. Materials should be fully tested by the end user to establish suitability of the product for the intended application. August 2024

Premier Sealant Systems Ltd.

T 01724 864 100 | E sales@sealprem.com | www.sealprem.com

Mercia Way, Foxhills Industrial Park, Scunthorpe, DN15 8RE

Registered Office: Mercia Way, Foxhills Industrial Park, Scunthorpe, DN15 8RE | Registered in Cardiff No. 3000843