

# Metallocene Polyolefin

## Product Description

Sealprem profiled foam fillers are designed to seal roofing and cladding profiles against dust, water and water vapour ingress.

## Features

Sealprem fillers are supplied:

- Made to measure
- With extended base
- Ventilated
- In a range of materials, thicknesses & colours
- In spacer & strip form
- Angle-cut

## Typical Applications

- Sealing eaves and ridge
- Sealing hips and valleys
- Sealing rooflights

|                                      | Black   | White   |
|--------------------------------------|---|---|
| Type                                 | High tensile  | High tensile  |
| Material                             | Fully closed-cell metallocene catalysed polyolefins | Fully closed-cell metallocene catalysed polyolefins |
| Thickness                            | 25mm +/-2mm   | 25mm +/-2mm   |
| Density (kg/m <sup>3</sup> )         | 24  | 33  |
| Service temperature (°C)             | -70 to +100   | -70 to +100   |
| Durability (dependent on conditions) | 25 + years  | 25 + years  |
| UV stability                         | Sensitive to UV                                     | Sensitive to UV                                     |

Please note: The above technical information is given as a guide and is based on recent test data obtained under laboratory conditions. Materials should be fully tested by the end user to establish suitability of the product for the intended application. August 2024

### Premier Sealant Systems Ltd.

T 01724 864 100 | E [sales@sealprem.com](mailto:sales@sealprem.com) | [www.sealprem.com](http://www.sealprem.com)

Mercia Way, Foxhills Industrial Park, Scunthorpe, DN15 8RE

Registered Office: Mercia Way, Foxhills Industrial Park, Scunthorpe, DN15 8RE | Registered in Cardiff No. 3000843