

# AirSeal 310 FR

## Product Description

Halogen free, polymer emulsion-based cartridge sealant. It is easily applied and dries to a flexible and smooth surfaced material which provides movement capability in fire rated linear joint and penetration seals. It is readily over paintable. It has excellent adhesion to a wide range of substrates and will not harden or crack with age.

## Features

- Fire tested to the requirements of BS EN 1366-4 (linear gaps)
- Tested to the requirements of ETAG 026 Parts 2 & 3 to demonstrate durability (Appendix A)
- BS EN 1634-1 2014 + A1 2018 – FD30 & FD60
- BS EN ISO 10140-2. 2010 Measurement of Airborne Sound Insulation of Building elements. University of Salford reports 2612-76;77 and 79 to 81. The sealant maintained the integrity of a plasterboard partition wall with a Sound Reduction Index of 55dB. Install as per guidance within BR211
- VOC test report classification – M1 and Indoor Air Comfort GOLD®
- Forms a fire and smoke seal in joints up to 35mm wide without slumping

## Typical Applications

- Air and Vapour Control Membranes
- In and around internal partitions where flexibility may be required
- Linear gap seals. Vertical or horizontal at head or foot of wall

	Value
Movement Accomodation	+/-12.5% Conforms to ISO 11600 F 12.5P
Durability (ETAG 026-2&3)	Category Z1 (-10/+70°C) suitable for intended use at temperatures between -10°C and +70°C) internal use high humidity
Skinning Time	15 minutes to 1 hour depending on conditions
Cure Time	5 to 15 days for 15mm x 20mm bead
Hardness Shore A	35-45
Tensile Strength (100%)	0.2 MPa
Paintability	With most paints when cured
Application Temperature	+5 to +40°C
Cleaning	Uncured sealant with water
Specific Gravity	1.60 - 1.68
Shelf Life	Minimum 24 Months in unopened containers
Colour	Blue

## Application Instructions

To achieve a high-quality joint, ensure surfaces are dry and free of all dirt, oil, and loose material, using a wire brush if necessary. Non porous surfaces should be degreased using a suitable degreasing agent. Highly porous surfaces should be sealed with a suitable primer. For a cleaner finish, apply masking tape to each side of joint and gun sealant firmly into joint, smoothing off with a wet spatula. Masking tape should be removed within 10 minutes of application.

## Coverage

1 tube is sufficient to produce approx. 1m using a 20mm x 15mm bead.

## Storage

Store in cool dry conditions, and protect from frost.

## Other Notes:

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable; each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

Please note: The above technical information is given as a guide and is based on recent test data obtained under laboratory conditions. Materials should be fully tested by the end user to establish suitability of the product for the intended application. March 2024

---

### Premier Sealant Systems Ltd.

T 01724 864 100 | E [sales@sealprem.com](mailto:sales@sealprem.com) | [www.sealprem.com](http://www.sealprem.com)

Mercia Way, Foxhills Industrial Park, Scunthorpe, DN15 8RE

Registered in Cardiff No. 3000843