

DPT514CW Double Coated Polyester Tape

Product Description

DPT514CW is a high performance double coated clear Polyester tape.

Features

- High performance acrylic pressure sensitive adhesive system
- High tack and shear strength
- Excellent low and elevated temperature performance
- Superior moisture resistance in high humidity

Applications

The product is specified by Kingspan for use on their Topdek Insulated Single Ply Roofdeck system to ensure a flat side lap detail when using mechanical hot air welding equipment.

Physical information

	Value
Thickness	0.089mm
Dimensions	50mm x 50m
Adhesion : Peel	14.2 N/2.5cm
: Shear	Indefinite @ 15.2 kPa
: Tack	Rolling ball – 25.4mm
Tensile	33.9 N/2.5cm
Elongation	100%
Minimum Application Temperature	- 23 °C
Continuous Use Temperature Range	-27 °C to + 149 °C
Release Liner	90 GSM Super Calendered Kraft

Please note: The above technical information is given as a guide and is based on recent test data obtained under laboratory conditions. Materials should be fully tested by the end user to establish suitability of the product for the intended application. August 2024

Premier Sealant Systems Ltd.

T 01724 864 100 | E sales@sealprem.com | www.sealprem.com

Mercia Way, Foxhills Industrial Park, Scunthorpe, DN15 8RE

Registered in Cardiff No. 3000843