

SealPrem Ready-Mixed Plaster

Product Description

Lightweight ready to use compound specially developed for filling gypsum board joints. Product is tested according to EN 13963 and meets the requirements of CE marking 4A. That means being able to use as a tapeless jointing compound.

Features

- No need to use reinforcement tapes
- Very low shrinkage
- Very high crack resistance
- Quick drying
- Sandable
- Paintable

Typical Applications

- For filling and finishing of gypsum board joints and plastering of screw heads in plasterboard systems.
- Can be used without reinforcement tapes on tapered, half-rounded tapered and half-rounded factory gypsum board edges

Adhering to:

- Gypsum board
- Wood
- Masonry
- Treated metals

	Value
Basis	Acrylic
Consistency	Non-slump paste
Density (DIN 53 479-B)	0.4g/ml
Tack free time	<10min
Skin forming time	4-6min
Loss of volume (ISO 10563)	3-5%
Service temperature	+5 °C to +75 °C
Application temperature	+10°C to +40°C
Shelf life	24 months
Shore A hardness (ISO 868)	70
Resistance to flow (ISO 7390)	0mm
Colour	White
Package	5 litre bucket, 16 litre bucket

Premier Sealant Systems Ltd.

T 01724 864 100 | E sales@sealprem.com | www.sealprem.com

Mercia Way, Foxhills Industrial Park, Scunthorpe, DN15 8RE

Registered in Cardiff No. 3000843

Application Instructions

Application conditions:

Application temperature between +10°C and +40°C.

Surface preparation:

The surfaces must be dry, clean from dust, loose particles and oil. Non-porous surfaces should be cleaned with solvent and a clean, non-fluffy cotton cloth. Solvent excess should be removed before evaporating with a clean cloth.

Application method:

Room and surface temperature must be at least +10°C. The gypsum wall surface should be stable, dry, firm, clean, and even. It should meet all requirements provided by gypsum board producer. Joint between two gypsum boards must be 2-4mm. Remove any existing release agents, paste or paper residue, make sure that the joints and gypsum board surface is dust free. In case there is a need of using two layers of gypsum boards then joints of the first layer must be filled with the product as well. After substrate's preparation fill the joint using small putty knife and press the filler into the joint firmly by moving the putty knife across the joint. Remove excess filler with wider putty knife. The joint treated with the product can be sanded, plastered and painted after drying in 4-6 hours. The consumption rate to fill tapered factory edge and half-rounded tapered factory edge is 0,2l/m.

Cleaning

Uncured acrylic can be removed with water or with special cleaning wipes. Cured acrylic should be first removed mechanically and then with a moist cloth.

Storage conditions and shelf life

Guaranteed shelf life 24 months from the manufacturing date when stored in closed original package in a dry place at temperatures between +5°C and +30°C. Avoid freezing and temperatures over +30°C.

Limitations

- PlasterSeal is not suitable for gypsum boards with a beveled cut edge or mixed edge
- Not suitable in application constant contact with water and damp or wet conditions
- Avoid using on bituminous and tar-containing substrates
- Not suitable for moveable joints
- Avoid using on substrates that bleed oils and plasticizers
- Best not to use with untreated metals due to oxidation risk
- Due to the wide variety of possible substrates, we recommend a preliminary compatibility and adherence test
- Due to the wide variety of influences during and after application, the customer must always test the product first
- Please observe the expiration date!

Safety regulations

Ensure sufficient ventilation during application and wear necessary personal protective equipment. More specific safety information is available on the safety data sheet (SDS).

Technical classification and certificates

- EN 13963:2005: Type 1A

Please note: The above technical information is given as a guide and is based on recent test data obtained under laboratory conditions. Materials should be fully tested by the end user to establish suitability of the product for the intended application. May 2024

Premier Sealant Systems Ltd.

T 01724 864 100 | E sales@sealprem.com | www.sealprem.com

Mercia Way, Foxhills Industrial Park, Scunthorpe, DN15 8RE

Registered in Cardiff No. 3000843