

# SealPrem SilAcryl Elastic Acrylic Silicone

## Product Description

Elastic paintable decoration sealant based on silanized acrylic dispersion. Suitable for interior and exterior applications.

## Features

- Low odour
- Interior and exterior use
- Excellent for movable joints
- Remains elastic
- Bright white extra smooth surface
- Easy to clean

## Typical Applications

- Excellent for applications where regular acrylic may fail
- Joints between window and wall
- Inner wall corners
- Joints between door frame and wall

## Adhering to:

- Concrete
- Masonry
- Gypsum board
- Wood
- PVC
- Glass
- Ceramics
- Treated metals

	Value
Density (DIN 53 479-B)	1.42 g/ml
Tack free time	8-10 min
Resistance to flow (ISO 7390)	0 min
Intensity of microbiological grows (ISO 846)	2
Application temperature	+5°C to+40°C
Service temperature	-30°C to+75°C
Shelf life	18 months
Shore A hardness (ISO 868)	8-12
E-Modulus 100% (ISO 37) cured	0.32N/mm <sup>2</sup>
Tensile strength (ISO 37) cured	0.39N/mm <sup>2</sup>
Elongation at break (ISO 37) cured	>300%
Colour	White

### Premier Sealant Systems Ltd.

T 01724 864 100 | E sales@sealprem.com | [www.sealprem.com](http://www.sealprem.com)

Mercia Way, Foxhills Industrial Park, Scunthorpe, DN15 8RE

Registered in Cardiff No. 3000843

Package

300 ml cartridge

## Application Instructions

Application conditions:

Application temperature between +5°C and +40°C.

Surface preparation:

The surfaces must be dry, clean from dust, loose particles and oil. Non-porous surfaces should be cleaned with solvent and a clean, non-fluffy cotton cloth. Solvent excess should be removed before evaporating with a clean cloth.

Application method:

Cartridge: cut off the threaded end of the cartridge and screw on the application nozzle for directing sealant. Cut the threaded end in a way where a suitable opening for application is produced. Place the cartridge together with the applicator in the gun and fill the installation nozzle with sealant, by repeatedly pressing the gun trigger.

Foil package: open the end of the foil pack and place the pack inside the gun so that the dosing nozzle keeps covering its open portion. Place the dosing nozzle on the open end and screw on the cap to close the tube. Cut the nozzle to create a suitable opening for dosing sealant.

Apply sealant in the joint by repeatedly and evenly pressing on gun trigger and smoothly dragging the nozzle along the joint. After application, smooth the surface with a suitable tool (e.g., spatula) and remove excess material.

Paintable after the final curing. Curing time depends on the size of the joint (2,5-3 mm/day). Early painting can cause cracking of the paint. It is strongly recommended to cover cured caulk with a suitable paint to guarantee its longevity and similar colour shade with the background surface.

Cleaning:

Uncured acrylic can be removed with water or with special cleaning wipes. Cured acrylic should be first removed mechanically and then with a moist cloth.

## Storage conditions and shelf life

Guaranteed shelf life 18 months from the manufacturing date when stored in closed original package in a dry place at temperatures between +5°C and +30°C. Avoid freezing and temperatures over +30°C. Short-term resistance to freezing, max 10 days at temperatures over -18°C. Freeze-thaw resistance 7 cycles at temperatures -18°C and +23°C, one cycle lasting 48 hours (24 hours at -18°C and 24 hours at +23°C).

## Limitations

- It should not be applied on bituminous or tar containing substrates, and to materials that bleed oils or plasticizers. Do not use in damp or wet conditions or if rain is imminent.
- Not recommended for applications in constant contact with water.
- Early painting may cause cracking of the paint
- Not suitable for joints with movement more than 12,5% of the joint width.
- Due to the wide variety of possible substrates, we recommend a preliminary compatibility and adherence test. If necessary, prime surfaces to improve adhesion.
- Due to the wide variety of influences during and after application, the customer must always test the product first.
- Please observe the expiration date!

**Premier Sealant Systems Ltd.**

T 01724 864 100 | E [sales@sealprem.com](mailto:sales@sealprem.com) | [www.sealprem.com](http://www.sealprem.com)

Mercia Way, Foxhills Industrial Park, Scunthorpe, DN15 8RE

Registered in Cardiff No. 3000843

## Safety regulations

Ensure sufficient ventilation during application and wear necessary personal protective equipment. More specific safety information is available on the safety data sheet (SDS).

## Technical classification and certificates

- Sealant for facade for interior and exterior application, suitable for cold climate.  
EN 15651-1:2012: Type F-INT-EXT-CC: CLASS 12,5E
- Suitable for use in HVAC systems in accordance with VDI6022, tested in accordance with EN ISO 846.

Please note: The above technical information is given as a guide and is based on recent test data obtained under laboratory conditions. Materials should be fully tested by the end user to establish suitability of the product for the intended application. May 2024

---

### **Premier Sealant Systems Ltd.**

T 01724 864 100 | E [sales@sealprem.com](mailto:sales@sealprem.com) | [www.sealprem.com](http://www.sealprem.com)

Mercia Way, Foxhills Industrial Park, Scunthorpe, DN15 8RE

Registered in Cardiff No. 3000843