

Firestop 700

Product Description

Premier Firestop 700 is a low modulus, one part, neutral curing, fire-rated silicone sealant.

Features

- Excellent unprimed adhesion to a range of substrates, including stone, steel, masonry, brick and wood
- Tested to BS476 Part 22/1987
- Meets ISO 11600-F&G-25LM
- Up to 4-hour fire rating in certain configurations

Typical Applications

- The provision of fire-rated systems where expansion joints or penetration seals are required in curtain walling, building facades or partition walls
- Expansion joints and pipe/cable penetrations in fire-rated structures



Firestop 700	
Adhesion	Excellent to stone, steel, masonry, brick and wood
Colours	White
Slump	1mm max.
Working time	15 minutes
Tack free time (23°C)	1.5 hours
Joint movement capability	± 50%
Application temperature	+5°C to +40°C
Expected life	20 years
Shelf life	6 months

Please note: The above technical information is given as a guide and is based on recent test data obtained under laboratory conditions. Materials should be fully tested by the end user to establish suitability of the product for the intended application. October 2014

Premier Sealant Systems Ltd

Mercia Way Foxhills Industrial Park Scunthorpe, DN15 8RE, England

Tel. 01724 864100 | Fax. 01724 860116 | Email. sales@premseal.co.uk | Website. www.premseal.co.uk