

# Ancillary Products

## Aluminium Foil Tape with Liner

### Product Description

A soft-tempered bright aluminium foil tape coated with a high-tack pressure adhesive which has excellent UV light resistance. Supplied on a white glassine liner.

### Features

- Good adhesion
- Easy to tear by hand



### Typical Applications

- Alleviation of moisture vapour transmission on foil faced insulation boards
- Double glazing industry

	With Liner
Foil thickness	30 micron
Shear (static)	87 hours @ 1kg
Elongation	5%
Loop tack	800 N/m
Peel adhesion to steel	1000 N/m
Fire protection	Class 0 BS476 part 7 1987
Minimum application temperature	0°C
Tensile Strength	50 N/25 mm
MVTR	1g/m <sup>2</sup> /24hr
Service temperature	-20°C to +120°C
Shelf life	1 year

*Please note: The above technical information is given as a guide and is based on recent test data obtained under laboratory conditions. Materials should be fully tested by the end user to establish suitability of the product for the intended application. October 2014*

#### Premier Sealant Systems Ltd.

T 01724 864 100 | E [sales@sealprem.com](mailto:sales@sealprem.com) | [www.sealprem.com](http://www.sealprem.com)

Mercia Way, Foxhills Industrial Park, Scunthorpe, DN15 8RE

Registered Office: 19 Titan Court, Luton, LU4 8LL | Registered in Cardiff No. 3000843