

Ancillary Products

EPDM Bubble Gasket

Product Description

EPDM Bubble Gasket is a closed-cell expanded EPDM cellular rubber sealing strip. 95mm x 10mm x 40m VJ2 gasket.

Features

- Classified to ASTM D-1056, RE45, B2, C1
- Adheres to clean and dry surfaces



Typical Applications

- Air and water seal in cladding systems

EPDM Bubble Gasket	
Base material	EPDM
Colour	Black
Density	0.8 – 0.9 g/cm ³
Ozone resistance	Excellent
Service temperature	-50°C to +90°C
Application temperature	Above 0°C
Shelf life	1 year
Surface preparation	Clean, dry and grease-free
Compression Set 22hrs	50%RT 25%Max
Weather Resistance	No Cracks
Compression Deflection 25%	17-24psi
Heat Aging 7 Days	70° Deflection Change +/- 30%

Please note: The above technical information is given as a guide and is based on recent test data obtained under laboratory conditions. Materials should be fully tested by the end user to establish suitability of the product for the intended application. October 2014

Premier Sealant Systems Ltd.

T 01724 864 100 | E sales@sealprem.com | www.sealprem.com

Mercia Way, Foxhills Industrial Park, Scunthorpe, DN15 8RE

Registered Office: 19 Titan Court, Luton, LU4 8LL | Registered in Cardiff No. 3000843