

Polyethylene

Product Description

Premseal profiled foam fillers are designed to seal roofing & cladding profiles against dust, water and water vapour ingress..

Features

Premseal fillers are supplied:

- Made to measure
- Ventilated
- In a range of materials, thicknesses & colours
- With extended base
- In spacer & strip form
- Angle-cut



Typical Applications

- Sealing eaves and ridge
- Sealing hips and valleys
- Sealing rooflights

	J25	J30	J50
Type	Standard	Standard	Standard
Material	Fully closed cell cross linked PE	Fully closed cell cross linked PE	Fully closed cell cross linked PE
Colour	Black, White Black and white mixed	Black, White	Black, White
Thickness	25mm	30mm	30mm
Density (kg/m ³)	30	30	30
Service temperature (°C)	-70°C - 100°C	-70°C - 100°C	-70°C - 100°C
Durability	20 years	20 years	20 years

Please note: The above technical information is given as a guide and is based on recent test data obtained under laboratory conditions. Materials should be fully tested by the end user to establish suitability of the product for the intended application. October 2014

Premier Sealant Systems Ltd

Mercia Way Foxhills Industrial Park Scunthorpe, DN15 8RE, England

Tel. 01724 864100 | Fax. 01724 860116 | Email. sales@premseal.co.uk | Website. www.premseal.co.uk