

Material Safety Datasheet: SGRP10



DATE: 17.03.2014 (EU/453/2010 – EC/1907/2006) DOC.: MSDS-POC74-EN-0314

1 / IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY

Product name: SGRP10

Product type: Combination of modified butyl adhesive with PET reinforcement. This MSDS applies to the following products: SGRP10.

2/. HAZARDS IDENTIFICATION

2.1 Identification: Product does not meet classification and labeling criteria given in directive EC1272/2008. Under normal industrial conditions, there is no indication that the product can be considered as a health risk.

2.2 Labeling elements: None

2.3 Other hazards: PBT: no vPvB: no

3/.COMPOSITION

Butyl tape based on non-hazardous polymers as classified by EC1272/2008

Composition Range % Symbols R-phrases

This product does not contain hazardous components

4/. FIRST AID MEASURES

Symptoms and effects: Due to concentration ingestion, skin contact, or inhalation of sufficient quantities to induce symptoms is unlikely.

First aid - inhalation: Inhalation of sufficient quantities to induce symptoms is unlikely. First

aid - skin: Thoroughly wash exposed area with soap and water, get medical attention if reaction develops and irritation persists.

First aid - eye: May cause eye irritation if wiped or rubber comes in contact; seek medical attention if irritation persists.

First aid - ingestion: Ingestion of sufficient quantities to induce symptoms is unlikely. Apply for medical advice. Do not induce vomiting.

5/. FIRE–FIGHTING MEASURES

Extinguishing media: Use water, foam or dry powder to extinguish.

Unsuitable extinguishing media: No limitation known.

Dangerous decomposition products:

Combustion may yield several by-products: CO, CO₂, various hydrocarbons, H₂S, SO_x (sulfur oxides), sulfuric acid and unidentified inorganic compounds. To prevent environmental damage, if possible collect water used to extinguish the fire in basins.

Protective equipment: Follow normal firefighting procedures. Fire-fighters should wear self contained breathing apparatus, especially in enclosed areas.

6/.ACCIDENTAL RELEASE MEASURES

Personal precautions: No special precautions required.

Environmental precautions: No special precautions required.

Clean-up methods - Small spillage:

Collect into container and dispose in accordance with local regulations.

Clean-up methods - Large spillage:

Collect into container and dispose in accordance with local

regulations. 7 / HANDLING AND STORAGE

Handling: No special precautions required. Good industrial and personal hygiene practice should be followed. No eating, drinking and smoking in the workplace. Storage: Store between +5 °C and + 30 °C. Store dry in the original packaging.

8 / EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering control measures: No special precautions required, good industrial and personal hygiene practice should be followed. No eating, drinking and smoking in the workplace. Use the best available methods of handling for our products whereby the employees enjoy the maximum safety and whereby the environment is minimally taxed.

9 / PHYSICAL AND CHEMICAL PROPERTIES

Physical state +20°C: Solid

Form: Solid, tape

Odour: Not applicable

Colour: Grey Relative density: ≥ 1.30 g/cm³

Viscosity: Not applicable

Boiling point / range: Not applicable

Melting point/range: Not established

Flash point: Not established

Flammability: Not established

Auto ignition temp.: > 200°C

Explosion properties: Not applicable

Vapour density: Not applicable

Vapour pressure: Not applicable

Solubility in water: Not soluble

Solubility in solvents: Soluble

pH: Not applicable

Partition coefficient n-octanol/water:

Not established

10 / STABILITY/REACTIVITY

Stability: Stable under recommended storage conditions.

Conditions to avoid: Open flames.

Materials to avoid: No materials to avoid.

Hazardous decomposition products:

Premier Sealant Systems Ltd

www.premseal.co.uk | sales@premseal.co.uk | Tel. 01724 864100 | Fax. 01724 860116

Mercia Way, Foxhills Industrial Park, Scunthorpe, DN15 8RE

Registered Office: 19 Titan Court, Luton, LU4 8LL | Registered in Cardiff No. 3000843

Under normal conditions of storage and use, hazardous decomposition products should not be produced. (incomplete) Combustion may yield several by-products: CO, CO₂, various hydrocarbons, H₂S, SO_x (sulfur oxides), sulfuric acid and unidentified inorganic compounds.

11 / TOXICOLOGICAL INFORMATION

Basis for assessment: Low toxicity is indicated by available data. Under normal industrial conditions, there is no indication that the product can be considered as a health risk.

12 / ECOLOGICAL INFORMATION

Mobility: Not mobile.

Persistence/degradability: Product is hardly degradable.

Bioaccumulation: There is seemingly no tendency for bioaccumulation.

Ecotoxicity: Product is not toxic.

13 / DISPOSAL CONSIDERATIONS

Waste disposal: All product disposals should comply with local, national or EEC regulations.

Product disposal: All product disposals should comply with local, national or EEC regulations.

14 / TRANSPORT INFORMATION

Transport road and rail: UN Number ADR/RID Correct technical name ADR/RID ADR/RDI Class

Packaging group

The product is not classified as dangerous for transport.

Transport air: UN number ICAO Proper shipping name ICAO Class

The product is not classified as dangerous for transport.

Transport sea: UN Number IMO Proper shipping name IMDG Class Packing Group

The product is not classified as dangerous for transport.

15 / REGULATORY INFORMATION

EU Classification: Not applicable.

EU Symbols: Not applicable.

EU Risk phrases: Not applicable.

EU Safety phrases : Not applicable.

16/. STORAGE AND TRANSPORTATION ADVICE

STORAGE TEMPERATURE: between 5 °C and 25 °C Ambient

TRANSPORT TEMPERATURE: between 5 °C and 25 °C Ambient

LOADING/UNLOADING TEMPERATURE: Ambient

VISCOSITY (cSt): Not Applicable

STORAGE/TRANSPORT PRESSURE (kPa): Atmospheric

ELECTROSTATIC ACCUMULATION HAZARD? No, not from product, slight static charge may be developed from the removal of the release paper, if relevant use appropriate grounding procedures

USUAL SHIPPING CONTAINERS: This product can be transported by shipping container. Where possible avoid any

excessive heat and prolonged exposure. Continuous exposure may impact on ease of application. Supplied in cardboard cartons.

MATERIALS AND COATINGS UNSUITABLE: None

STORAGE / HANDLING, GENERAL NOTES: Store in a cool, well-ventilated place away from incompatible materials. Do NOT remove release liner or store cartons of product near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Shelf life more than 24 months in ambient conditions.

Storage temperatures between 5 °C and 25 °C would be advisable however storage outside of these temperatures is possible hence the terms cool and ambient.

The key to keeping material fit for purpose is to keep it dry.

IF STORAGE AND TRANSPORTATION IS BELIEVED TO BE BEYOND THESE CONDITIONS PLEASE CONTACT US TO DISCUSS FURTHER.

17/. OTHER INFORMATION

Disclaimer: This Material Safety Data sheet conforms to EEC Directive EU/453/2010 – EC/1907/2006.

The information given here is to the best of our knowledge true and accurate. As our company has no indication of the application and conditions where our products are used, the user must take the necessary precautions to guarantee safety and the environment. No responsibility can arise or be derived from this document, neither can any guarantee or warranty be given for results in the end use. It is the responsibility of the user to ensure that during handling, storage and use of the product all regulations to protection of man and environment are observed. This sheet is not a sales specification or an indication of suitability for a particular use. This material Safety Data Sheet will replace all previous versions.

Premier Sealant Systems Ltd

www.premseal.co.uk | sales@premseal.co.uk | Tel. 01724 864100 | Fax. 01724 860116

Mercia Way, Foxhills Industrial Park, Scunthorpe, DN15 8RE

Registered Office: 19 Titan Court, Luton, LU4 8LL | Registered in Cardiff No. 3000843

