

EPDM Primer

Product Description

EPDM Primer is a one part, solvent containing, air-drying polyacrylate/silane blend based primer.

MAIN APPLICATIONS

Recommended for use in conjunction with the Arbo Membrane System for use with Arbo SA and Arbo Membrane Adhesive. Recommended for the priming of porous surfaces such as sound concrete, cementitious boards, timber and other porous surfaces. EPDM Primer is easy to apply and very convenient for large surface area applications.

NB

Due to the variety of substrates available it is recommended that a trial application is carried out before construction commences.

APPLICATION INSTRUCTIONS

The joint surfaces must be clean, dry and free from all contamination. The surfaces should be degreased using the appropriate Arbo Cleaner. Apply EPDM Primer using a clean dry brush or roller and allow to dry for a least 1 hour but not more than 8 hours before applying the adhesive.

Features

- Joint Size Suitability – The joint width should be at least 6mm in order that the joint faces can be cleaned and primed correctly.
- Storage Life – 6 months in original unopened package stored in a cool, dry place out of direct sunlight.
- Coverage – Approximately 6 square metres per litre dependent upon porosity of the substrate.
- Health & Safety – EPDM Primer is labelled as harmful and Highly Flammable. For full information please refer to Material Safety Data Sheet.
- Packaging – EPDM Primer is supplied in 1 litre containers.



Please note: The above technical information is given as a guide and is based on recent test data obtained under laboratory conditions. Materials should be fully tested by the end user to establish suitability of the product for the intended application. Nov 2020

TECHNICAL DATA

Colour:	Colourless
Density:	Approx 0.95 g/cm ³
Application Temperature:	+ 5o C to + 30o C
Cleaning:	Tools must be carefully cleaned immediately after use with an appropriate cleaner.

Please note: The above technical information is given as a guide and is based on recent test data obtained under laboratory conditions. Materials should be fully tested by the end user to establish suitability of the product for the intended application. Nov 2020

Premier Sealant Systems Ltd.

T 01724 864 100 | E sales@sealprem.com | www.sealprem.com

Mercia Way, Foxhills Industrial Park, Scunthorpe, DN15 8RE

Registered Office: 19 Titan Court, Luton, LU4 8LL | Registered in Cardiff No. 3000843