

## Sealprem Porous Primer

### Product Description

Sealprem Porous Primer is a one part, solvent containing, air drying isocyanate resin-based primer.

#### MAIN APPLICATIONS

Recommended for use in conjunction with Arbokol AG2 and Arbokol 2150 two-part polysulphide sealants for the priming of porous surfaces such as concrete, block-work, brickwork etc.

#### APPLICATION INSTRUCTIONS

The joint surfaces must be clean, dry and free from all contamination. The surfaces should be degreased using the appropriate Arbo Cleaner. Apply one coat of Arbokol AG2 Porous primer using a clean dry brush and allow it to dry for a least 1 hour but not more than 8 hours before applying the sealant.

All joint preparation and priming should be carried out in accordance with BS 8000 Part 16, the British Standard for the sealing of joints in buildings using sealants.

### Features

- Joint Size Suitability – The joint width should be at least 6mm in order that the joint faces can be cleaned and primed correctly.
- Storage Life – 9 months in original unopened packaging stored in a cool, dry out of direct sunlight.
- Health and Safety – Sealprem Porous Primer is labelled as Harmful and Highly Flammable. For full information please refer to Material Safety Data Sheet.
- Packaging – Sealprem Primer is supplied in 500ml and 5 Litre containers.  
N.B Yield approximately 125 metres per 500ml, 1250 metres per 5 litre.



*Please note: The above technical information is given as a guide and is based on recent test data obtained under laboratory conditions. Materials should be fully tested by the end user to establish suitability of the product for the intended application. Feb 2019*

Technical Data	
Colour:	Colourless, yellowish
Density:	Approx 1.0 g/cm <sup>3</sup>
Application Temperature:	+ 5°C to + 30°C
Cleaning:	Tools must be carefully cleaned immediately after use with an appropriate cleaner.

*Please note: The above technical information is given as a guide and is based on recent test data obtained under laboratory conditions. Materials should be fully tested by the end user to establish suitability of the product for the intended application. Feb 2019*

---

**Premier Sealant Systems Ltd.**

T 01724 864 100 | E [sales@sealprem.com](mailto:sales@sealprem.com) | [www.sealprem.com](http://www.sealprem.com)

Mercia Way, Foxhills Industrial Park, Scunthorpe, DN15 8RE

Registered Office: 19 Titan Court, Luton, LU4 8LL | Registered in Cardiff No. 3000843