

## FR Breather Membrane Lap Tape

### Product Description

Breather Membrane Lap Tape is a sealing and bonding tape suitable for sealing laps on Breather Membranes within both roof and wall applications. It should be used in conjunction with Double-Sided Adhesive Lap Tape for a fully sealed and airtight membrane installation.

Manufactured with high strength acrylic dispersion adhesive, and using non-woven polypropylene as the carrier, Breather Membrane Lap Tape is the perfect tape to use with installation of Breather Membranes. This will help to ensure an airtight seal of the external building envelope helping to keep heat in, while allowing moisture to leave the building.

This tape is required for use with some breather membranes in accordance with BS 5534 wind uplift requirements. Please see individual breather membrane technical datasheet for guidance and geographical data.



### Features

- \*B-s1,d0 fire rated when fitted to A1 / A2 materials, D-s2,d0 when on wood
- Excellent UV stability. TPU performs significantly better than other materials. Install as per BS 5534 UV guidance
- CE compliant to EN 13859-1 (roofs) and EN 13859-2 (walls)
- Waterproofing membrane suitable for walls over 18 metres
- Single product for all roofs and walls
- Monolithic breathable / vapour
- permeable membrane design
- High performance TPU / non-woven laminate construction
- Suitable for use on fully boarded roofs

### Roll Detail

Roll size	50mm x 25m
Release paper	Brown silicone paper
Carrier	Polypropylene non-woven

*Please note: The above technical information is given as a guide and is based on recent test data obtained under laboratory conditions. Materials should be fully tested by the end user to establish suitability of the product for the intended application. October 2014*

#### Premier Sealant Systems Ltd

Mercia Way Foxhills Industrial Park Scunthorpe, DN15 8RE, England

Tel. 01724 864100 | Fax. 01724 860116 | Email. sales@premseal.co.uk | Website. www.premseal.co.uk

Adhesive	Acrylic dispersion
Shelf life	12 months, stored in original packing at 21°C and 50% relative humidity

*Please note: The above technical information is given as a guide and is based on recent test data obtained under laboratory conditions. Materials should be fully tested by the end user to establish suitability of the product for the intended application. October 2014*

---

**Premier Sealant Systems Ltd**

Mercia Way Foxhills Industrial Park Scunthorpe, DN15 8RE, England

**Tel.** 01724 864100 | **Fax.** 01724 860116 | **Email.** [sales@premseal.co.uk](mailto:sales@premseal.co.uk) | **Website.** [www.premseal.co.uk](http://www.premseal.co.uk)